

Description: 1 conductor 24 AWG stranded bare copper, polyethylene insulated, overall conductive vinyl and copper serve shielded, PVC jacketed guitar cable

VTG Part Number: INST1.

1. Conductor

1.1 AWG Size and Stranding: 24 AWG 19 strands 36 AWG

1.2 Material: Bare annealed copper

2. Insulation

2.1 Material: Polyethylene

2.2 Wall Thickness: .045" nominal

2.3 Diameter: .116" +/- .002"

3. Shield

3.1 Type: Composite conductive vinyl and copper serve

3.2 Inner Layer

3.2.1 Material: Semi-conductive PVC

3.2.2 Wall Thickness: .010" nominal

3.2.3 Diameter: .136" nominal

3.3 Outer Layer

3.3.1 Material: Bare annealed copper serve

3.3.2 Coverage: 70% nominal

4. Jacket

4.1 Material: Matte finish polyvinyl chloride

4.2 Jacket Colors: Black, blue, green, neon blue, neon green, neon orange, neon pink, neon yellow, purple, red, white, and yellow

4.3 Wall Thickness: .045" nominal

4.4 Diameter: .242" +/- .005"

5. Markings

5.1 Type: Surface printing in white ink (blue ink on white jacket)

5.2 Legend: VTG AUDIO LOW NOISE – INSTRUMENT CABLE MADE IN U.S.A.

VTG AUDIO NEON BRITES GUITAR/INSTRUMENT CABLE MADE IN U.S.A.

6. Electrical Specifications

6.1 Capacitance: 25 pF/ft @ 1 kHz

6.2 Characteristic Impedance: 60 ohms @ 1 MHz

6.3 Resistance at 20C: 23 Ohms/1000 ft.



Dr. No.: 0713A-01

By: TRM

Date: 05/14/97

Page 1 of 1