

CAP-2 HDMI to USB 3.0 Capture Box

Input	1x HDMI
Output	1x USB 3.0 (Type A)
Input Video Bandwidth	150MHz
Output Video Bandwidth	Up to 350Mbps (USB)
Supported Input & Output Video Formats	<ul style="list-style-type: none"> • 1920 x 1080p 60/59.94/50/30/29.97/25/24/23.976 • 1680 x 1050p 60 • 1600 x 1200p 60 • 1440 x 900p 75/60 • 1400 x 1050p 60 • 1366 x 768p 60 • 1360 x 768p 60 • 1280 x 1024p 75/60 • 1280 x 720p 60/59.94/50 • 1024 x 768p 75/60 • 800 x 600p 75/60 • 720 x 576p 50 • 720 x 480p 60 • 720 x 576i 50 • 720 x 480p 60 • 640 x 480p 75/60
Supported Output Video Formats	<ul style="list-style-type: none"> • 1920 x 1080p 60/50/30/25/24 • 1680 x 1068p 60 • 1440 x 1080p 60 • 1440 x 896p 60 • 1360 x 768p 60 • 1280 x 768p 60 • 1280 x 720p 60/50 • 1024 x 768p 60 • 960 x 536p 60 • 848 x 480p 60 • 768 x 576p 60 • 720 x 480p 60/50 • 640 x 480p 60 • 640 x 360p 60
Audio Input	HDMI Embedded Audio & Line in Stereo
Audio Support	2 Channel, 44.1 and 48KHz sample rate, up to 24 bit PCM
Recording Mode	Software Compression
Recording Video Format	YUY2 (USB3.0), MJPG (USB2.0/3.0)
Firmware update	USB Port
Software Compatibility	<ul style="list-style-type: none"> • Windows: Amcap, Google Plus Hangouts, OBS (Open Broadcast Software), Skype, VLC, Xsplit Broadcaster, Zoom.us • Linux: VLC, OBS • Mac OS X: OBS, Quicktime player, VLC, Facetime
Power Supply	Via USB
Power Consumption	2W
Operation Temperature	0~40C [32~104F]
Storage Temperature	-20~60C [-4~140F]
Humidity	20~90% RH
Dimension (L x D x H)	105 (L) x 68 (D) x 23 (H)mm