

**DAC-70 Up / Down / Cross Converter**

|                               |  |
|-------------------------------|--|
| Conversion                    | VGA/HDMI/SDI to HDMI/SDI<br>Multi-format Up/Down/Cross   |
| Video Inputs                  | 1x VGA, 1x HDMI,<br>1x 3G/HD/SD-SDI (support Level A and Level B)  |
| Loop Through                  | Yes  |
| Video Outputs                 | 2x 3G/HD/SD-SDI with embedded Audio (support Level A and Level B)<br>1x HDMI   |
| Audio Inputs                  | 2x RCA (Stereo Pair), 2x SDI/HDMI Audio embedded   |
| Audio Outputs                 | SDI embedded audio up to 8CH, 48KHz, PCM audio<br>HDMI embedded audio up to 8CH, 48KHz, PCM audio  |
| Supported Video Input Formats | 1080p(23.98/24/25/29.97/30/50/59.94/60Hz),<br>1080psf(23.98/24/25/29.97/30Hz), 1080i (50/59.94/60Hz), 720p (50/59.94/60Hz),<br>625i, 576p, 576i, 525i, 480p, 480i, 1920x1080(60Hz), 1280x720(60Hz), 1600x1200(60Hz),<br>1400x1050(60Hz), 1366x768(60Hz), 1280x1024(60Hz), 1024x768(60Hz), 800x600 (60Hz) |
| Output Resolutions            | 1080p(23.98/24/25/29.97/30/50/59.94/60Hz), 1080i (50/59.94/60Hz), 720p (50/59.94/60Hz),<br>625i, 525i  |
| Equalizer                     | Yes  |
| Reclock                       | Yes  |
| SDI Cable Drive               | Yes  |
| Dimension (LxWxH)             | 112 x 85 x 45 mm   |
| Weight                        | 0.4 kg   |
| Operating Temp. Range         | 0~40 °C  |
| Power                         | DC 12V, 6W   |
| What's in the Box             | 1 x DAC-70<br>1 x AD Switch DC 12V<br>1 x DIP switch Pin 8 label<br>1 x Thank You Card   |