

PTC-140TH HDBaseT PTZ Camera with HBT-11 Receiver

Video format	1080p 60/59.94/50/30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50
Image Sensor	1/2.8 inch high quality HD CMOS sensor
Effective Pixels (approx.)	2.07 Mega pixels
S/N Ratio	>55dB
Min. Illumination	0.5Lux (F1.8, AGC ON)
Electronic Shutter	Auto / Manual
Zoom Ratio	20x Optical Zoom, 10x Digital Zoom
Gamma Control	Off / Normal
Iris Control	Auto / Manual
Digital Noise Reductions	Yes
On-Screen Display (OSD)	English, Simplified Chinese
White Balance	Auto, Manual, One Push, 3000K, 4000K, 5000K, 6500K
AGC / Gain Control	Auto / Manual
Mirror / Flip Image	Yes
Focus Mode	Auto / Manual
Panning / Tilting Range	Pan: 340° , Tilt: +90° to -30°
Panning / Tilting Speed	Pan: 0.1~60°/sec Tilt: 0.1~30°/sec
Preset	255 Position
Focal Length	f=5.2 (wide) to 98 (tele) mm F1.6 to F3.5
Field of View (Horizontal, Wide)	Approx. 54.7° (WIDE END) / 3.3° (TELE END)
Image Compensation	Backlight Compensation
Video Output	HDBaseT (PoE) x1 RJ-45 x1
Audio Input	Line In (IP Stream Output)
Tally LED	Dual color (Red, Green)
Filter	M52.0 x 0.75 Thread with UV Protection
Protocol	VISCA, DVIP
Remote Control Interface and Transmit Distance	RS-232 Lan (RJ-45) HDBaseT (RJ-45)/ DVIP on Receiver Box: Transmit up to 100m
Video Compression Format	H.264, H.265, Dual stream output
Audio Compression Format	AAC/MP3/PCM Audio compression
HD IP Interface	100M IP port(100BASE-TX); Support DVIP
Network Protocol	RTSP, RTMP
F/W Update	Ethernet
IR Control	Yes
Camera Control Unit	HS-1500T/HS-1600T/RMC-180/RMC-300C
Tripod Mount	1/4-20 UNC
Options	WM-1
Color	Black/White
Dimension (LxWxH)	156 x 182 x 186 mm
Weight	1.6 kg

Operating Temp. Range	0~40 °C
Power	DC 12V 12W
What's in the Box	1 x PTC-140T Main Unit 1 x IR remote controller 1 x PTC-140T Thank You Card 1 x HBT-11 Main Unit 1 x Phoenix connector to RJ-45 1 x HBT-11 Thank You Card 1 x Ceiling mount bracket-A 1 x Ceiling mount bracket-B 6 x Ceiling mount bracket screw M3*4mm 1 x UV Filter 1 x PTC-140T DC 12V Power Adaptor 1 x HBT-11 DC 48V Power Adaptor 2 x Power Cord 1 x A tightrope 1 x RS-232 DB9 9 Pin to 8 Pin Mini DIN Cable