

SOUND MASKING LOUDSPEAKER

# Quam MA/E9/S2/T8

MA/E9/S2/T8 is an 617 CID, ceiling grid mount, sound masking loudspeaker assembly consisting of an 8" O.D., dual cone loudspeaker with a 10 oz. magnet and a 4W, 70V rotary select transformer. Support chain is supplied.



<b>APPLICATION</b>	<b>Intended Use:</b>	Indoor environment
	<b>Program Material:</b>	Equalized random noise
	<b>Secondary Use:</b>	Signal tones or equalized voice
	<b>Installation:</b>	Placed upward-facing on 24" wide ceiling tile on conventional suspended ceiling grid
<b>AUDIO PERFORMANCE</b>	<b>Average Sensitivity:</b>	95dB SPL, 1W/1M
	<b>Loudspeaker Power Rating:</b>	20W RMS, EIA 426A Standard
	<b>Calculated Output:</b>	101dB SPL, 4W/1M
	<b>Magnet Type &amp; Weight:</b>	BeFe Ceramic, 10 oz.
	<b>Frequency Response:</b>	65Hz - 17kHz, EIA 426A Standard
	<b>Nominal Coverage Angle:</b>	100° Included Angle, -6dB/2kHz, Half Space
	<b>Audio Connection:</b>	7", Color-coded, Pre-cut and Tinned Leads
	<b>Mechanical Connection:</b>	Seismic tie-offs provided on top of unit if required by AHJ
<b>COMPONENT</b>	<b>Unit Dimension:</b>	3 7/16" (H) x 23 3/4" (W) x 11 13/16" (D) x
	<b>Weight:</b>	7 lbs.
	<b>Loudspeaker Model:</b>	8C10PAX
	<b>Loudspeaker Specs:</b>	8" O.D., dual cone loudspeaker, 10 oz. magnet
	<b>Transformer:</b>	4W, 70V, rotary select with 5 taps (0.25W, 0.50W, 1W, 2W, 4W)

