

SURFACE MOUNT LOUDSPEAKER

Quam SYSTEM 2

SYSTEM 2 is a complete loudspeaker system consisting of an 8" O.D., dual cone loudspeaker and a 5W, 25/70V transformer mounted on a square, screw mount, steel baffle with a slanted, steel, vandal resistant, surface mount enclosure with four (4) 8-32 threaded inserts, a single 1/2" conduit entrance on the back, and two (2) Wiremold knockouts and a white, powder coat finish.



| | | |
|--------------------------|---|---|
| APPLICATION | Intended Use: Program Material: Installation: | Indoor environment Signal tones, voice and music Horizontal or vertical surface mount |
| AUDIO PERFORMANCE | Average Sesitivity: Loudspeaker Power Rating: Maximum Output: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection: | 92dB SPL, 1W/1M 12W RMS, EIA 426A Standard 15W @ 8 Ohms 99dB SPL, 5W/1M BeFe Ceramic, 5 oz. Nominal 65Hz - 17kHz EIA, 426A Standard 100° Included Angle, -6dB/2kHz, Half Space 7", Color-coded, Pre-tinned Leads |
| COMPONENT | Dimensions: Weight: Loudspeaker: Transformer: Baffle: Backbox: Finish: | 11 5/8" (H) x 11 5/8" (W) x 5 3/8" (D) 10 lbs. 8C5PAX TBLU: 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5.0W) BS8W SE2WVP with four (4) 8-32 threaded inserts White powder coat |

