

SE-2850 HD/SD 8/12-Channel Digital Video Switcher

Video Standard	HD & SD
Video Format	3G/HD/SD input: 1080i 50/59.94/60Hz 1080p 25/30/59.94/60Hz HD Output: 1080p 25/29/30Hz 1080i 50/59.94/60Hz SD: 576i 50Hz, 480i 59.94Hz
Video Processing	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
Input Routable / Crosspoint	All 12, repeatable
Video Input	Standard: 8x SDI, 2x HDMI Max: 12x SDI, 3x HDMI
Mix HD & SD Source	Yes
Computer Graphic Interface	Max 3 via HDMI
Video Output	4x SDI assignable: PGM, PVW, AUX & Clean Out 2x HDMI assignable: PGM & multi-view
Down-converted Output	Yes, 4x SDI (CH1-CH4)
Built-in Multi-view Monitoring Out	2x HDMI
Audio Input	4x Balanced XLR
Audio Output	2x Balanced XLR
Embedded Audio Support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	Up to 8 frames per channel (*SDI input audio only)
A+V Switching	Yes
Title Creator	Yes
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
Picture in Picture	2
Logo Insertion	2 (or 1 logo + 1 clock)
Still Store	12
Effects	FTB, Cut, 8 Wipe with border
Transition Preview	PiP & DSK
Sync / Reference In/Out	Built-in Genlock Support external sync with loop thru
Tally Output	1x D-sub 25pin, dual color
PC Remote Control	Via Ethernet (free Window software) or RS-422
Special Features	4-CH SD downconvert output Built in TC-200 CG system Selectable SMPTE/EBU Audio level
Chassis	2 units, 2RU rack-mount mainframe
Dimension (LxWxH)	433 x 312 x 76 mm (switcher) 432 x 252 x 88 mm (main unit)
Weight	4.7 kg
Power	DC 12V, 44W
Operating Temp. Range	0~40 °C
Options	CB-46/47/60/61/62

What's in the box

1 x SE-2850 Main Unit
1 x SE-2850 Control Board
1 x AD Switch DC 12V with AC Cord
1 x DB9P TO DB9P Cable
1 x CB-41 / XLR to XLR Cable
2 x Extra button cap for wipe
12 x Screw
2 x 2U Ear Rack
1 x Thank You Card