

GS 60

GARDEN SPEAKER

DESCRIPTION

GS 60 is an outdoor speaker suitable for gardens that includes a 5" coaxial loudspeaker and an internal transformer for 100V / 70V constant voltage lines. GS 60 can be placed on several surfaces, such as wood, concrete or into the ground.



FEATURES

- Body made of linear low-density polyethylene
- Coaxial transducer with 5,25"oofer and 1,20" tweeter
- Suitable for installation on different surfaces
- Can be used in constant voltage lines 100V / 70V or in low impedance (8 ohm)
- Protection grade IP56



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-10dB):	60 Hz ÷ 20000 Hz
	Max SPL @ 1m:	111 dB
	System Sensitivity:	90 dB
Power section	Nominal Impedance (ohm):	8 ohm
	Power Handling:	60 W RMS
	Peak Power Handling:	240 W PEAK
	Recommended Amplifier:	120 W
Transducers	Dome Tweeter:	1.3"
	Woofer:	5.5"
Input/Output section	Constant Voltage Transformer:	70/100 V
	Power selection 1 (100 V):	32 W - 313 ohm
	Power selection 2 (100 V):	16 W - 625 ohm
	Power selection 3 (100 V):	8 W - 1250 ohm
	Power selection 4 (100 V):	4 W - 2500 ohm
	Power selection 5 (100 V):	2 W - 5000 ohm
	Power selection 6 (100 V):	1 W - 10000 ohm
Standard compliance	IP protection grade:	IP 56
	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	PE Low Density
	Color:	Green
Size	Height:	409 mm / 16.1 inches
	Diameter:	365 mm / 14.37 inches
Shipping informations	Package Height:	460 mm / 18.11 inches
	Package Width:	440 mm / 17.32 inches
	Package Depth:	440 mm / 17.32 inches
	Package Weight:	5.74 kg / 12.65 lbs

PART NUMBER

· 13133084

GS 60

EAN 8024530012090



DRAWINGS

