

## XA65 XA60

		XA65	XA60			
Sensor		1/2.3-inch 4K UHD CMOS sensor				
Lens	Zooming ratio, focal length (35 mm camera equivalent)	20x optical zoom, approx. 29.3 - 601mm 4K UHD (Dynamic IS off/Standard IS on) / approx. 30.5 - 627mm Full HD (Dynamic IS off/Standard IS on)				
Lens	Aperture	8 blades				
	Image Stabilizer	Optical + electronic correction				
Infrared camera supported		YES				
Monitor		3.5-inch (approx. 2.76 million dots), LCD, Capacitive touch panel				
EVF		0.36-inch (approx. 1.77 million dots), OLED, tiltable				
Looks		Standard				
Movie recording	MXF	YES (XF-AVC)				
	AVCHD	NO				
	MP4	YES				
	LPCM 4ch audio	YES (not available during 720 recording)				
	Simultaneous Recording	Double recording				
	OSD Recording	YES				
	Slow and Fast (S&F) Motion Recording	YES				
	Cinema-look filters	NO				
Recording Media	Built-in memory	NO				
	Memory card	SD card (2 slots)				
Professional use terminals	SDI terminal	YES (3G-SDI)	NO			
	GENLOCK, TC	NO				
	XLR terminal (INPUT 1, INPUT 2)	YES				
Other terminals		HDMI, separate headphones, USB (USB Type-C), DC IN (USB Type-C), remote and MIC terminal (supports plug-in power)				
Accessory shoe		Handle unit: Cold shoe				
Detachable handle		YES (XLR terminal, built-in infrared light, mic holder, cold shoe, zoom leve trigger, tally lamp)				
Wi-Fi		NO				

		XA65	XA60			
GPS		NO (Accessories supported)				
Lens hood with barrier		YES				
Dimensions		Approx. 4.3 x 3.3 x 7.2 in. / 109 x 84 x 182mm				
Weight	Body only	Approx. 1.65 lbs. / 750 g	Approx. 1.63 lbs. / 740 g			
	Lens hood, mic holder unit, handle unit, BP-820 and memory card (1 pc) included	Approx. 2.51 lbs. / 1140 g	Approx. 2.50 lbs. / 1135 g			

Recording Mode	[Main operation] SD Card recording			SDI/HDMI output				
	Resolution	Frame rate	Color format	Color depth	Resolution	Frame rate	Color format	Color depth
	3840x2160	29.97p			1920x1080	29.97p	4:2:2	8 bit
						59.94i		
					1280x720	59.94p		
		23.98p			1920x1080	23.98p		
						59.94i		
					1280x720	59.94p		
					1920x1080	59.94p		10 bit
		59.94p				59.94i		
XF-AVC			4:2:0	8 bit	1280x720	59.94p		
	1920x1080	59.94i			1920x1080	59.94i		
					1280x720	59.94p		
					1000 1000	29.97p		
		29.97p			1920x1080	59.94i		
					1280x720	59.94p		
		23.98p			1920x1080	23.98p		
						59.94i		
					1280x720	59.94p		
	3840x2160	29.97p	4:2:0	8 bit	1920x1080	29.97p		8 bit
		23.98p				59.94i		
MP4	1920x1080	59.94p				23.98p		
						59.94i		
						59.94p		10 bit
		29.97p				59.94i		
					1280x720	59.94p	4:2:2	
					1920x1080	29.97p		
		23.98p				59.94i		
					1280x720	59.94p		
					1920x1080	23.98p		
	1280x720	59.94p				59.94i		
					1280x720	59.94p		