

# Blackmagic Videohub 40x40 12G



Blackmagic Videohub 40x40 12G is an advanced zero latency video router that supports any combination of SD, HD and Ultra HD on the router at the same time. It has 40 12G-SDI inputs and 40 12G-SDI outputs, redundant power and reference connections in two rack units size. The large full HD LCD lets you see video before routing and clearly displays routing labels and video standards. Routing can be performed by direct button selection and using the large spin knob control that has an electronic clutch. It also features SDI re-clocking, external Ethernet control and supports all SDI video standards up to 2160p60.

\$3,995

#### Connections

**SDI Video Inputs** 

40

**SDI Video Outputs** 

40

**SDI Rates** 

DVB-ASI, 270Mb, 1.5G, 3G, 6G, 12G.

Video Input Re-Sync

None

SDI Reclocking

On all SDI outputs.

Reference Inputs

Tri-Sync or Black Burst.

**Reference Outputs** 


Reference terminating loop output.

**Ethernet** 

Supports 10/100/1000 BASE-T.

**Computer Interface** 

USB-C



#### Standards

#### SD Video Standards

525i59.94 NTSC, 625i50 PAL

#### **HD Video Standards**

720p50, 720p59.94, 720p60 1080i50, 1080i59.94, 1080i60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p47.95, 1080p48, 1080p50, 1080p59.94, 1080p60 1080PsF23,98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30

#### 2K Video Standards

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI, 2Kp29.97 DCI, 2Kp30 DCI, 2Kp47.95 DCI, 2Kp48 DCI, 2Kp50 DCI, 2Kp59.94 DCI, 2Kp60 DCI 2KPsF23.98 DCI, 2KPsF24 DCI, 2KPsF25 DCI, 2KPsF29.97 DCI, 2KPsF30 DCI

#### Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30, 2160p47.95, 2160p48, 2160p50, 2160p59.94, 2160p60

#### 4K Video Standards

4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI, 4Kp29.97 DCI, 4Kp30 DCI, 4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI, 4Kp59.94 DCI, 4Kp60 DCI

#### **SDI Compliance**

SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 424M, SMPTE 425M level A and B SMPTE 2081-1, SMPTE 2081-10, SMPTE 2082-10, ITU-R BT.656 and ITU-R BT.601

## **SDI Audio Sampling**

Television standard sample rate of 48kHz and 24-bit.

#### SDI Video Sampling

YUV 4:2:2 and RGB 4:4:4

#### **SDI Color Precision**

10, 12-bit RGB 4:4:4 in all HD and 2K modes, Ultra HD modes up to 2160p30 and 4K modes up to 4Kp30 DCI. 10-bit YUV 4:2:2 in all modes.

#### SDI Color Space

REC 601, REC 709, REC 2020

#### SDI Auto Switching

Automatically selects between 270Mb SD-SDI, 1.5G HD-SDI, 3G level A and level B HD-SDI, 6G HD-SDI, 12G-SDI and DVB-ASI on each input so that each input can be running a different television standard.

#### SDI Metadata Support

Video payload identification ancillary data as per SMPTE 352M.

## Control

#### **Built in Control Panel**

24 buttons for local control of Videohub with 3 buttons and search dial for menu control. 5 inch color display.

#### **External Control Panel**

Includes Blackmagic Videohub software control panel for Mac and Windows. Supports Videohub Smart Control Pro and Videohub Master Control Pro hardware panels. Includes Blackmagic Videohub SDK and Ethernet Videohub Control Protocol.

#### **Control Panel Connection**

Ethernet

## Software

#### **Software Control**

Router control included free for Windows<sup>TM</sup> and Mac $^{TM}$ .

### Internal Software Upgrade

Via included updater application.

# **Operating Systems**



Mac 12.0 Monterey, Mac 13.0 Ventura or later.



Windows 10, 64-bit. Windows 11.

# Display

#### **Displays**

Built in 5 inch LCD for video and menu settings.

# Power Requirements

# **Power Supply**

 $2\ x$  Internal 100 - 240V AC 50/60Hz. IEC power cables required.

#### **Power Fail Protection**

Crosspoint connections preserved and restored instantly at power on.

# Power Usage

46.5 W max.

# Physical Installation

2 rack units height.

# Physical Specifications



# **Environmental Specifications**

Operating Temperature	Storage Temperature	Relative Humidity
0° to 40° C (32° to 104° F)	-20° to 60° C (-4° to 140° F)	0% to 90% non-condensing

# What's Included

Blackmagic Videohub 40x40 12G Welcome wallet with QR code for software download

# Warranty

3 Year Limited Manufacturer's Warranty, and 12 Month Warranty on the front panel.

Blackmagic Design Authorized Reseller	

All items on this website are copyright Blackmagic Design Pty. Ltd. 2023, all rights reserved. All trademarks are property of their respective owners. MSRP includes