

Assembling Instructions for the KS7350 FOLDING Z KEYBOARD STAND

SETUP

- 1. Remove unit from box and inner bag.**
- 2. Unthread both female knobs with washers from the treaded stud located where the horizontal and vertical square tubing of the box beam are connected.**
- 3. Take the two folded rectangular sections and swing the upper and lower support arms all the way until they lock into their position to make two Z sections.**
- 4. (This might require two people)With the threaded studs facing each other place the box beam onto the threaded studs making sure the box beam sits flush with the side arms of the box beam go around the front and back of the vertical rectangular tubing. Note the width adjusting knobs on the box beam and the height adjusting knobs should be facing the same direction. Secure box beam in place with the female knobs with washers.**
- 5. Adjust the width of the stand by loosening the two male knobs on the box beam and adjust to your desired position making sure not to have less then 3" over hang for your equipment on either side. Tighten width adjusting knobs.**
- 6. Adjust height of the stand by loosening the large knobs on the vertical rectangular tubing. The first height position is with the inner rectangular tube all the down inside outer rectangular tube.**
- 7. The second height position is when you raise the inner rectangular tubes to the first hole with a horizontal notch. Position the horizontal notch on both sides so it positioned right at the top of the outer tube. Secure the height adjustment knobs.**

- 8. Follow step 7 for third to and including the sixth height positions.**

Before you proceed or put any equipment on your stand is to make sure that all knobs are tightened to prevent any damage to your equipment or personal injury.

9. **Place two foam rest pads on the upper support arms
So your equipment will not rest on the metal of the support arms**
10. **Carefully place your equipment on the stand and make sure you do not have less than 3" of overhang on either side. If you have less than 3" remove your equipment from the stand and see step 5.**

NEVER move or adjust your stand with equipment on it to prevent damage to the stand, your equipment, or personal injury

Folding up for Carrying or Storage

1. **Remove your equipment from the stand.**
2. **Loosen height adjusting knobs on both upper supports and position them all the way down. Tighten the knobs**
3. **(This might take two people) Remove the female knobs with washers holding the box beam assembly to the Z sections. Remove the box beam.**
4. **Take each of the Z sections and unlock the upper and lower support arms and swing them all the way around until they are positioned against the center vertical rectangular tube.**
5. **Place the two folded Z sections against each other with the threaded studs facing up and the height adjusting knobs facing each other.**
6. **Loosen knobs on box beam.**
7. **Place box beam on the threaded studs making sure the box beam is sitting flush and the box beam is not longer than the folded Z sections. Place washers and thread female knob on each threaded stud and tighten knobs.**
8. **Make sure all knobs are tightened before carrying.**

Optional Accessories

**KSB-6500 Keyboard Stand Bag
KSA7550 Second Tier
KT7800 3-Position X-Style Bench
KT7800+ 4-Position X-Style Bench**